FUSION® SERIES



WHAT YOU NEED TO KNOW

MULTIPLE INSTALLATION AND ORDERING OPTIONS

Can be installed on 12" on-centers up to 32". For a complete installation order the LTMUP Tilt Mount and Power Conditioner Kit (includes LTMU and PAC521P).

OTHER PRODUCT OPTIONS




LTA

FUSION Wall Mount
- For flat panels 37-63"



RLT2

FIT™ Hinge Mount





PWC

Tilt Wall Mount with CPU Storage



RXT2

FIT™ Hinge Mount

- For flat panels 40-63"

FEATURES

CONTROLZONE™ LEVELING

Industry-first feature allows post-installation fine tuning of height and leveling, up to 0.5" (13 mm) adjustment up or down.

CENTRIS' LOW-PROFILE TILT

Centris fingertip tilt technology uses the center of gravity to balance the screen while maintaining a low profile under 2" (51 mm) deep! Screen angle stays set in place until readjusted.

CENTERLESS™ SHIFT

Provides up to 17.5" (445 mm) of postinstallation lateral shift – 8.75" (222 mm) left/right of uprights – for limitless centering capabilities.

CLICKCONNECT*

Hear an audible click when the screen safely engages with the mount. A built-in cable stand provides easy access under the screen.

SPECIFICATIONS

Depth from Wall	1.98" (50 mm)
Tilt*	-12°
Max Lateral Shift	17.5" (445 mm)
Dimensions (HxWxD)	16.5 x 34.44 x 1.99" (419 x 875 x 51 mm)
Max Mounting Pattern (H,W)	19.88" (505 mm) 35.35" (895 mm)
Color	Black
Weight Capacity	200 lbs (90.7 kg)

^{*} Varies with screen height.

RECOMMENDED ACCESSORIES



FVS250 ■ 12" (305 mm) Video Conferencing Shelf - above



FCS100 ■ Single Component Shelf - below



FLR100 Left/Right Speaker Adapter

For a complete list of FUSION accessories see pages 86 - 88.

TECHNICAL DRAWINGS

